

Kiosks, Counters & Closet Shutters by Alutech



Roll Shutters provide a perfect barrier for counter applications where a quick and easily operated security shutter is needed. Alutech shutters can be designed for installation on the interior and exterior of any application for an appealing look. Our end slat can be securely locked with slide bolt or key lock for maximum protection.

Alutech Shutters are perfect for Kiosks, Counters and Closets. Our shutters have also been used to lock down refrigerated P.O.P. units in airports, medical offices and customized jewelry cases.

800-233-1144, www.alutech.com



RC*40 Aluminum Foam Filled Slat

The RC*40 Roll Formed Foam Filled Slat is the most commonly used shutter slat in today's market. It is a versatile slat that conveniently rolls small and with its polyurethane foam core insulates and reduces unwanted outside noise levels.

Available Colors: White, Light Beige, Cream, Gray and Brown

TECHNICAL SPECIFICATIONS	
Covering Surface	1 9/16" (40 mm)
Slat Height	1 9/16" (40 mm)
Nominal Thickness	3/8" (8.5 mm)
Design Weight per Square Foot	.88 lbs.
Slats per Square Foot	7.62
Recommended Maximum Width	118" (9.8 LF) (3.0 m)
Recommended Maximum Height	102" (8.5 LF) (2.6 m)
Minimum Roll Diameter	40 mm

HOUSING SIZE SELECTION CHART		Maximum Guide Rail Heights					
Housing Size	5 1/2"	6 1/2"	7"	8"	9"	10"	12"
Axle Size 40 mm	32 1/2"	62 1/2"	81"	103"			
Axle Size 60 mm	30 1/2"	49 1/2"	65"	96"	139"	165"	229"
Axle Size 70 mm		57"	88"	128"	159"	229"	

RC*37 Aluminum Foam Filled Slat

The RC*37 Roll Formed Foam Filled Slat is the most commonly used shutter slat when the housing size needs to be as small as possible. It is a versatile slat that rolls very small and with its polyurethane foam core insulates and reduces unwanted outside noise levels.

Available Colors: White, Light Beige, Cream, Gray, Brown, Black and Silver

TECHNICAL SPECIFICATIONS	
Covering Surface	1 7/16" (37 mm)
Slat Height	1 5/8" (41 mm)
Nominal Thickness	17/64" (7 mm)
Design Weight per Square Foot	.70 lbs.
Slats per Square Foot	7.03
Recommended Maximum Width	102" (8.5 LF) (2.6 m)
Recommended Maximum Height	102" (8.5 LF) (2.6 m)
Minimum Roll Diameter	40 mm

HOUSING SIZE SELECTION CHART		Maximum Guide Rail Heights					
Housing Size	5 1/2"	6 1/2"	7"	8"	9"	10"	12"
Axle Size 40 mm	59 3/4"	90 3/4"	112"	132 1/2"			
Axle Size 60 mm	40 1/2"	66 1/2"	82"	121"	146"	179"	
Axle Size 70 mm							



H25 Guide Rail	2 1/8" Mini Guide Rail Applicable Slats: RC*40, US*40, RCE*40 w/4mm Brush Insert. Accepts all 5 1/2" thru 10" 90° End Caps. Accepts all 5 1/2" thru 9" 45° End Caps.
H40 Guide Rail	2 5/8" Mini Guide Rail Applicable Slats: RC*40, US*40, RCE*40 w/4mm Brush Insert. Accepts all 5 1/2" thru 10" 90° End Caps. Accepts all 5 1/2" thru 9" 45° End Caps.



**ALUTECH
UNITED, INC**

Alutech United, Inc. Alutech United, Inc. 800-233-1144
15 Dixon Street 1537 Northgate Blvd. www.alutech.com
Selbyville, DE 19975 Sarasota, FL 34234

302-436-6005 941-355-0970

302-436-5100 Fax 941-355-0972 Fax